

BPK

Plastic Blank Plates



BPK-RF: Snap function, tool-free assembly



BPK: screwable

Product Description

BPK Blank plates seal cut-outs for standard 10-pole / 16-pole / 24-pole industrial connectors with IP rating up to IP64.

Plastic blank plates are available in two different versions:

- Type BPK: Blank plates for screw connection
- Type BPK-RF A: Blank plates for snapping into metal sheet plates up to a thickness from 1.5 to 3 mm

Advantages & Benefits

- Fast mounting of the blank plates BPK-RF range by snapping into the cut-out
- Integrated circular sealing (up to IP64)

Specifications

Material	Polypropylene (PP)
Flame class	UL94-V0
IP rating	BPK: IP64 BPK-RF A: IP54
Operating temperature	- 30°C to + 140°C (static) - 22°F to + 284°F (static)
Properties	Halogen free, silicone free

Compatible with

FP Flange plates 178 - 183

Type	Order No.	Blank plate for KEL cut-out	Dimensions	PU
BPK Blank plates for screw connection:				
BPK-B	42010	KEL-B KEL-U-B KEL-ER-B KEL-QUICK-B	76 x 53 mm 2.992 x 2.087 "	10
BPK 10	42015	KEL 10 KEL-U 10 KEL-ER 10 KEL-QUICK 10	101 x 53 mm 3.976 x 2.087 "	10
BPK 16	42016	KEL 16 KEL-U 16 KEL-ER 16 KEL-QUICK 16	121 x 53 mm 4.764 x 2.087 "	10
BPK 24	42024	KEL 24 KEL-U 24 KEL-ER 24 KEL-QUICK 24 KEL-FG-A	148 x 53 mm 5.827 x 2.087 "	10
BPK Blank plates for snapping into cut-outs:				
BPK-B-RF A	42010.002	KEL-B KEL-U-B KEL-QUICK-B	76 x 53 mm 2.992 x 2.087 "	10
BPK 10-RF A	42015.002	KEL 10 KEL-U 10 KEL-QUICK 10	101 x 53 mm 3.976 x 2.087 "	10
BPK 16-RF A	42016.002	KEL 16 KEL-U 16 KEL-QUICK 16	121 x 53 mm 4.764 x 2.087 "	10
BPK 24-RF A	42024.002	KEL 24 KEL-U 24 KEL-QUICK 24 KEL-FG-A	148 x 53 mm 5.827 x 2.087 "	10
BPK-JFX	42620	KEL-JUMBO flex	88 x 88 mm 3.465 x 3.465 "	5