

## CONFIX SH

### Conduit Clips for WST



Type	Order No.	Suitable conduit	Fixing hole	Width [mm]	Height [mm]	PU
CONFIX SH 10	31300	NW 10	M3	18.5 0.728 "	21 0.827 "	10
CONFIX SH 14	31310	NW 14	M3	24 0.945 "	25.5 1.004 "	10
CONFIX SH 20	31320	NW 20	M5	35 1.378 "	36 1.417 "	10
CONFIX SH 23	31330	NW 23	M5	42 1.654 "	43.5 1.713 "	10
CONFIX SH 29	31335	NW 29	M5	48	48.5	10
CONFIX SH 37	31340	NW 37	M6	55 2.165 "	56.5 2.22 "	10
CONFIX SH 45	31350	NW 45	M6	67 2.638 "	68 2.677 "	10
CONFIX SH 70	31360	NW 70	M6	100 3.937 "	101 3.976 "	10

## Product Description

CONFIX SH Conduit clips are a one-piece clamping system to provide secure mounting points for corrugated conduit systems.

The clips are secured to their mounting position through a central mounting point with a hexagonal counter-bore.

## Specifications

Material	Polyamide (PA), black
Flame class	UL94-V2
Operating temperature	- 40°C to + 140°C - 40°F to +284°F
Properties	Halogen free, silicone free

## Compatible with

CONFIX WST  
Split corrugated conduit 160