

# FT Grommets for Flat Cables



1.11

Description	Type	Order No.	Clamping range	PU
	FT-1 0	46201	Blank grommet	5
	FT-1 A	46210	Width: 19 - 23 mm / 0.748 - 0.906 " Thickness: 5.5 - 6 mm / 0.217 - 0.236 "	5
	FT-1 B	46211	Width: 28 - 33 mm / 1.102 - 1.299 " Thickness: 5.5 - 6 mm / 0.217 - 0.236 "	5
	FT-1 C	46212	Width: 24 - 30 mm / 0.945 - 1.811 " Thickness: 8.5 - 9 mm / 0.335 - 0.354 "	5
	FT-1 E	46214	Width: 19 - 24 mm / 0.748 - 0.945 " Thickness: 6.5 - 7 mm / 0.256 - 0.276 "	5
	FT-1 F	46215	Width: 28 - 33 mm / 1.102 - 1.299 " Thickness: 9 - 9.5 mm / 0.354 - 0.374 "	5
	FT-2 0	46202	Blank grommet	5
	FT-2 A	46250	Width: 32.5 - 38 mm / 1.28 - 1.496 " Thickness: 5 - 5.5 mm / 0.197 - 0.217 "	5
	FT-2 B	46251	Width: 45 - 50.5 mm / 1.772 - 1.988 " Thickness: 6 - 6.5 mm / 0.236 - 0.256 "	5
	FT-2 C	46252	Width: 47 - 52 mm / 1.85 - 2.047 " Thickness: 9.5 - 10 mm / 0.374 - 0.394 "	5
	FT-2 F	46255	Width: 38 - 43 mm / 1.496 - 1.693 " Thickness: 12.5 - 13 mm / 0.492 - 0.512 "	5
	FT-2 G	46256	Width: 49 - 54 mm / 1.929 - 2.126 " Thickness: 5 - 6 mm / 0.197 - 0.236 "	5
	FT-3 0	46203	Blank grommet	5
	FT-3 A	46300	Width: 72 - 77 mm / 2.835 - 3.032 " Thickness: 5 - 5.5 mm / 0.197 - 0.217 "	5
	FT-4 0	46204	Blank grommet	5
	FT-4 A	46330	Width: 85 - 99 mm / 3.346 - 3.898 " Thickness: 4.2 - 5.2 mm / 0.165 - 0.205 "	5

## Product Description

FT grommets are used to route flat cables, e.g. in elevator construction. Suitable for cable entry frames KEL-FL.

Innovative construction of the grommets compensates for manufacturing inconsistencies in flat cables.

## Advantages & Benefits

- Routing of flat cables with various dimensions

## Specifications

Material	Elastomer
Flame class	UL94-V0
IP Rating	IP54
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free

## Compatible with

KEL-FL Cable entry frames 32