



# KBM Series

Window Type Current Transformer

- 1.15kV Insulation Voltage
- 4.0kV - 1min Withstanding Voltage
- 50/60Hz Frequency
- 40 Over current Strength
- IEC 60044-1 Standard

## Ordering Information

KBM - 25 , 1.0 Class , 5 VA , 100~150 / 5 A

①                      ②                      ③                      ④                      ⑤

①		②	③	④		⑤	Weight(g)	Certificates	Dimensions(mm)					
Type		Class	VA	Primary	Secondary									
Meter Type	25	1.0	5	100~150	5	500	CE		Protection					
			15	200~300								1		
Relay type		5P10	5	350~400	1									
Meter Type	03	1.0	5	120~150	5	700	CE		Protection					
			15	200~350								or		
			40	400~600								1		
Relay type		5P10	5	400~600	1									
Meter Type	05	1.0	5	200~300	5	800	CE		Protection					
			15	400~800								or		
			40	1000~2000								1		
Relay type		5P10	5	400~600	1									
Meter Type	08	1.0	5	100~250	5	1000	CE		Protection					
			15	300~400								or		
			40	500~2000								1		
			Relay type	5P10 or 5P20								5	400~800	
												15	1000~2000	
		5	700~800											
Meter Type	10	1.0	5	200~300	5	1300	-		Protection					
			15	400~500								or		
			40	600~3200								1		
			Relay type	5P10 or 5P20								5	350~600	
												15	1000~2000	
												40	3000~4000	
		5	700~800											
		15	2500~4000											
Meter Type	12	1.0	5	300~400	5	840	CE		Protection					
			15	500~800								or		
			40	1000~3200								1		
Relay type		5P10	5	1200~3000	1									
Meter Type	14	1.0	15	400~500	5	2000	-		Protection					
			40	600~6000								or		
			Relay type	5P10 or 5P20								15	1000~2500	
												40	3000~4000	
		15	3000~4000											
Meter Type	18	1.0	15	500~600	5	2700	-		Protection					
			40	700~7500								or		
			Relay type	5P10 or 5P20								15	1200~2500	
												40	3000~5000	
												15	3000~5000	
Meter Type	21	1.0	15	500~750	5	3200	-		Protection					
			40	800~8000								or		
			Relay type	5P10 or 5P20								15	1200~2000	
												40	3000~5000	
												15	2500~5000	
		40	6000~8000											