








# KEL-DP-E Cable Entry Plates



Also available in black.



Description	Type	Order No.	Cut-out [mm]	Number of cables	PU
	KEL-DP-E 46 7	<input type="checkbox"/> 43585 <input checked="" type="checkbox"/> 50585	46 × 18 / 1.811 x 0.709 "	5× max. 8.3 mm / 0.327" 2× max. 6.5 mm / 0.256 "	10
	KEL-DP-E 46 9	<input type="checkbox"/> 43587 <input checked="" type="checkbox"/> 50587	46 × 18 / 1.811 x 0.709 "	8× max. 6.5 mm / 0.256 " 1× max. 12.1 mm / 0.476 "	10
	KEL-DP-E 86 13	<input type="checkbox"/> 43581 <input checked="" type="checkbox"/> 50581	85 × 18 / 3.346 x 0.709 "	11× max. 8.3 mm / 0.327" 2× max. 6.5 mm / 0.256 "	10
	KEL-DP-E 86 17	<input type="checkbox"/> 43583 <input checked="" type="checkbox"/> 50583	85 × 18 / 3.346 x 0.709 "	16× max. 6.5 mm / 0.256 " 1× max. 12.1 mm / 0.476 "	10
	KEL-DP-E 112 16	<input type="checkbox"/> 43576 <input checked="" type="checkbox"/> 50576	112 × 18 / 4.409 x 0.709 "	4× max. 6.5 mm / 0.256 " 11× max. 8.3 mm / 0.327 " 1× max. 12.1 mm	10
	KEL-DP-E 112 21	<input type="checkbox"/> 43578 <input checked="" type="checkbox"/> 50578	112 × 18 / 4.409 x 0.709 "	16× max. 6.5 mm / 0.256 " 4× max. 8.3 mm / 0.327 " 1× max. 12.1 mm	10
	KEL-DP-S 69 8	<input type="checkbox"/> 43591 <input checked="" type="checkbox"/> 50591	69 × 10 / 2.717 x 0.394 " Edge radii R2	8× max. 7.5 mm / 0.295 "	10

\* Only valid for gray product types

## Product Description

KEL-DP-E entry plates are designed for routing cables without connectors. The KEL-DP products are a cost saving alternative to traditional cable glands. Ideal for high volume applications where conventional cable glands would normally be used. Simply make a small hole in the thin membrane and push the cables through. The KEL-DP-E provides protection IP64 / UL Type 12.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

A special rib ensures a centered fit in the cut-outs.

## Advantages & Benefits

- Fast and easy assembly, no tools required
- High cable density
- Very good strain relief on the cable bundle
- Cost-effective
- Hygienic design – free of dirt-collecting recesses
- For wall thickness 1.5 - 2.5 mm / 0.059 - 0.098 "

## Specifications

Material	Elastomer
Color	<input type="checkbox"/> gray (similar RAL 7035) <input checked="" type="checkbox"/> black
Flame class	UL94-Vo
IP rating	IP64 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Plate depth	5 mm / 0.197 "

## Accessories

ST-B Plugs 85