

KEL-DPZ-B

Cable Entry Plates



IP66



Also available in black.



Also available with threaded bushings.



Membrane on front

Product Description

2.1

The KEL-DPZ-B entry plates are designed for routing cables without connectors.

The assembly of the KEL-DPZ-B with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane and push the cables through. The KEL-DPZ-B provides strain relief and protection IP66 / UL type 12.

With an area of only 46 × 46 mm, up to 25 cables can be easily routed and sealed.




ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Advantages & Benefits

- Space saving shape
- Dual sealing of cables acc. to IP66/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

Specifications

Material	Frame: Polyamide (PA) Sealing plate: Elastomer
Color	■ gray (similar RAL 7035) ■ black
Flame class	UL94-Vo
IP rating	IP66 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	46 × 46 mm / 1.811 x 1.811 " / page 218 - 219
Plate depth	10 mm

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-B 13	■ 43794 ■ 50794	8× 3.2 - 6.5 mm / 0.126 - 0.248 " 4× 5 - 10.2 mm / 0.197 - 0.402 " 1× 16 - 22 mm / 0.63 - 0.866 "	10
	KEL-DPZ-B 17	■ 43796 ■ 50796	10× 3.2 - 6.5 mm / 0.126 - 0.248 " 4× 5 - 10.2 mm / 0.197 - 0.402 " 2× 7.5 - 12 mm / 0.295 - 0.472 " 1× 9 - 16.2 mm / 0.354 - 0.638 "	10
	KEL-DPZ-B 25	■ 43798 ■ 50798	25× 3.2 - 6.5 mm / 0.126 - 0.248 "	10

* Only valid for gray product types

Accessories

ST-B Plugs	85
FP Flanged plates	178 - 183