

KEL-DPZ-KL

Cable Entry Plates



IP65



Also available in black.



Membrane on front



Conical shape on back provides additional sealing and strain relief

Product Description

The cable entry plate KEL-DPZ-KL is designed for routing up to 72 cables without connectors. The assembly of the KEL-DPZ-KL with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-KL provides strain relief and protection IP65 / UL type 12.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.


The KEL-DPZ-KL matches on junction boxes KL by Rittal.

Advantages & Benefits

- Space saving shape
- Dual sealing of cables acc. to IP65/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

Specifications

Material	Frame: Stainless steel V2A, molded with elastomer Sealing plate: Elastomer Screws: Stainless steel V2A
Color	<input type="checkbox"/> gray (similar RAL 7035) <input checked="" type="checkbox"/> black
Flame class	UL94-Vo
IP rating	IP65 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	192 × 62 mm / 7.56 × 2.441"
Plate depth	4 mm / 0.157"

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-KL 72	<input type="checkbox"/> 43675.001	42× 3.2 - 6.5 mm / 0.126 - 0.248 " 21× 5 - 10.2 mm / 0.197 - 0.402 " 6× 9 - 16.2 mm / 0.354 - 0.638 " 3× 16 - 22 mm / 0.63 - 0.866 "	1
		<input checked="" type="checkbox"/> 43675.101		

* Only valid for gray product types

Accessories

ST-B Plugs 85