

# KEL-FG-B

## Flange Enclosures for Cable Entry



V2A  
anti-corrosive

Also available with stainless steel screws (V2A).



Slit KT grommets



1.11

Description	Type	Order No.	Grommets small   large	PU
	KEL-FG-B4	42330	4 -	1
	KEL-FG-B4 with V2A screws	42330.200	4 -	1
	KEL-FG-B1	42332	- 1	1
	KEL-FG-B1 with V2A screws	42332.200	- 1	1

### Product Description

The cable entry frames KEL-FG-B are suited for installation, sealing and strain relief of cables with connectors and conduits at an angle of 90° to the panel, enclosure or machine wall. A flat rubber gasket is included in the shipment.

### Advantages & Benefits

- Installation at an angle of 90° to the wall
- Mechanical protection of cable directly at the place of entry
- Protection against water spray and drips
- Warranty on pre-terminated cables remains
- Space saving shape
- Strain relief according to EN 62444
- High stability, vibration resistant

### Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo
IP Rating	IP54, with gasket and correct selection of the cable grommets
Operating temperature	- 40°C to + 140°C (static) - 40°F to + 284°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	46 x 36 mm / 1.811 x 1.378", Page 218 - 219

### Accessories

Cable grommets	48 - 52
KEL-EMC Grounding mounts	138 - 140
ST Plugs	53