

KEL-QTA

Split Cable Entry Plates



Product Description

The KEL-QTA easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

Advantages & Benefits






- Quick assembly without tools
- High cable density by using multi-position grommets
- Simple assembly and disassembly in case of change or service
- Routing of cables with and without connectors in a high density
- Suitable for standard industrial connector cut-outs

Specifications

Material	Elastomer
Flame class	UL94-V0
IP Rating	IP54, with correct selection of the cable grommets QT
Operating temperature	- 40°C to + 90°C (static) - 40°F to + 194°F (static)
Properties	Halogen-free, silicone-free
Frame depth	17 mm / 0.669 "
Type A:	For wall thickness 1.5 - 2.5 mm / 0.059 - 0.098 "
Type B:	For wall thickness 2.8 - 4 mm / 0.11 - 0.157 "

Accessories

QT Cable grommets	66
ST-B Plugs	85
FP Flange plates	178 - 183

Description	Type	Order No. Type A	Order No. Type B	Cut-out [mm]	Cables	PU
	KEL-QTA 24 2 -DP 18	43642	43643	112 x 36 / 4.409 x 1.378 "	pre-terminated 2x 1 - 15 mm / 0.039 - 0.591 " without connector 16x max. 7 mm / 0.276 " 1x max. 12 mm / 0.472 " 1x max. 16 mm / 0.63 "	10
	KEL-QTA 24 4	43644	43645	112 x 36 / 4.409 x 1.378 "	pre-terminated 4x 1 - 15 mm / 0.039 - 0.591 "	10
	KEL-QTA 10 1 -DP 18	43655	43658	65 x 36 / 2.56 x 1.378 "	pre-terminated 1x 1 - 15 mm / 0.039 - 0.591 " without connector 18x max. 5 mm / 0.197 "	10
	KEL-QTA 10 2 -DP 6	43656	43659	65 x 36 / 2.56 x 1.378 "	pre-terminated 2x 1 - 15 mm / 0.039 - 0.591 " without connector 6x max. 5 mm / 0.197 "	10
	KEL-QTA-B4	43660	-	46 x 46 / 1.811 x 1.811 "	pre-terminated 4x 1 - 15 mm / 0.039 - 0.591 "	10