RoHS Made in Germany

EMC Bracket for Cord Grips



Туре	Order No.	Shield diameter	PU
KVT-EMC-25 SKL 1.5-3	37180.1	1.5 - 3 mm 0.059 - 0.118 "	5
KVT-EMC-25 SKL 3-6	37180.2	3 - 6 mm 0.118 - 0.236 "	5
KVT-EMC-25 SKL 6-8	37180.3	6 - 8 mm 0.236 - 0.315 "	5
KVT-EMC-25 SKL 8-11	37180.4	8 - 11 mm 0.315 - 0.433	5
KVT-EMC-32 SKL 1.5-3	37181.1	1.5 - 3 mm 0.059 - 0.118 "	5
KVT-EMC-32 SKL 3-6	37181.2	3 - 6 mm 0.118 - 0.236 "	5
KVT-EMC-32 SKL 6-8	37181.3	6 - 8 mm 0.236 - 0.315 "	5
KVT-EMC-32 SKL 8-11	37181.4	8 - 11 mm 0.315 - 0.433	5



Product Description

The KVT-EMC brackets in combination with the split cord grips KVT and QVT combine routing, EMC shield grounding and strain relief. The connection to the ground potential is possible via the enclosure wall or an grounding tape.

Cables pass through the split cord grips and lead directly into the EMC clamps.

Separate functions (according to regulations) carried out quickly and easily!

Advantages & Benefits

- Simple and tool free assembly
- Large contact area
- Subsequent assembly possible
- Additional M5 hole for ground strap

Specifications

Material Carbon steel, zinc plated

Compatible with

KVT Split cord grips 40 - 46QVT Split cord grips 60 - 61