

PFS|SKL EMC Shield Clamps for Bus Bar



Type	Order No.	Shield diameter	PU
PFS SKL 1.5-3	36786.1	1.5 - 3 mm 0.059 - 0.118 "	10
PFS SKL 3-6	36786.2	3 - 6 mm 0.118 - 0.236 "	10
PFS SKL 6-8	36786.3	6 - 8 mm 0.236 - 0.315 "	10
PFS SKL 8-11	36786.4	8 - 11 mm 0.315 - 0.433 "	10
PFS SKL 11-17	36786.5	11 - 17 mm 0.433 - 0.669 "	10
PFS SKL 17-22	36786.6	17 - 22 mm 0.669 - 0.866 "	10
Bus bar 10 × 3 mm / 39.37 x 0.394 "	36100	10 × 3 × 1000 mm* 39.37 x 0.394 x 0.118 "	1

* Other lengths available on request

Product Description

PFS|SKL shield clamps care easy to use and effective in grounding single cable shields.

The PFS|SKL is mounted by snapping on a 10 × 3 mm bus bar.

Advantages & Benefits

- Large contact area
- Simple and tool-free mounting, easy assembly
- The spring design requires no adjustments and will permanently maintain contact to the cable shield
- Shock and vibration resistant, maintenance free
- Designed for high density applications

4.1

Specifications

Material

SKL-clamp **Spring steel, zinc plated**

PFS-foot **Spring steel**

Bus bar **Cu, tin plated, max. current: 140 Amps**

Accessories

KEL-EMC-PF Bracket 139

MF Supports for bus bars 187