

PFS2|SKL EMC Double Shield Clamps for Bus Bar



Type	Shield diameter Pos. 1	Shield diameter Pos. 2	Order No.	PU
PFS2 SKL 01	blank	1.5 - 3 mm / 0.059 - 0.118 "	36788.01	10
PFS2 SKL 02	blank	3 - 6 mm / 0.118 - 0.236 "	36788.02	10
PFS2 SKL 03	blank	6 - 8 mm / 0.236 - 0.315 "	36788.03	10
PFS2 SKL 04	blank	8 - 11 mm / 0.315 - 0.433 "	36788.04	10
PFS2 SKL 10	1.5 - 3 mm / 0.059 - 0.118 "	blank	36788.10	10
PFS2 SKL 11	1.5 - 3 mm / 0.059 - 0.118 "	1.5 - 3 mm / 0.059 - 0.118 "	36788.11	10
PFS2 SKL 12	1.5 - 3 mm / 0.059 - 0.118 "	3 - 6 mm / 0.118 - 0.236 "	36788.12	10
PFS2 SKL 13	1.5 - 3 mm / 0.059 - 0.118 "	3 - 6 mm / 0.118 - 0.236 "	36788.13	10
PFS2 SKL 14	1.5 - 3 mm / 0.059 - 0.118 "	8 - 11 mm / 0.315 - 0.433 "	36788.14	10
PFS2 SKL 20	3 - 6 mm / 0.118 - 0.236 "	blank	36788.20	10
PFS2 SKL 21	3 - 6 mm / 0.118 - 0.236 "	1.5 - 3 mm / 0.059 - 0.118 "	36788.21	10
PFS2 SKL 22	3 - 6 mm / 0.118 - 0.236 "	3 - 6 mm / 0.118 - 0.236 "	36788.22	10
PFS2 SKL 23	3 - 6 mm / 0.118 - 0.236 "	6 - 8 mm / 0.236 - 0.315 "	36788.23	10
PFS2 SKL 24	3 - 6 mm / 0.118 - 0.236 "	8 - 11 mm / 0.315 - 0.433 "	36788.24	10
PFS2 SKL 30	6 - 8 mm / 0.236 - 0.315 "	blank	36788.30	10
PFS2 SKL 31	6 - 8 mm / 0.236 - 0.315 "	1.5 - 3 mm / 0.059 - 0.118 "	36788.31	10
PFS2 SKL 32	6 - 8 mm / 0.236 - 0.315 "	3 - 6 mm / 0.118 - 0.236 "	36788.32	10
PFS2 SKL 33	6 - 8 mm / 0.236 - 0.315 "	6 - 8 mm / 0.236 - 0.315 "	36788.33	10
PFS2 SKL 34	6 - 8 mm / 0.236 - 0.315 "	8 - 11 mm / 0.315 - 0.433 "	36788.34	10
PFS2 SKL 40	8 - 11 mm / 0.315 - 0.433 "	blank	36788.40	10
PFS2 SKL 41	8 - 11 mm / 0.315 - 0.433 "	1.5 - 3 mm / 0.059 - 0.118 "	36788.41	10
PFS2 SKL 42	8 - 11 mm / 0.315 - 0.433 "	3 - 6 mm / 0.118 - 0.236 "	36788.42	10
PFS2 SKL 43	8 - 11 mm / 0.315 - 0.433 "	6 - 8 mm / 0.236 - 0.315 "	36788.43	10

Bus bar 10 × 3 mm / 0.394 x 0.118 "	10 × 3 × 1000 mm* / 0.394 x 0.118 x 39.37 "	36100	1
-------------------------------------	---	-------	---

* Other lengths available on request

Product Description

PFS2|SKL shield clamps are easy to use and effective in grounding single cable shields.

The PFS2|SKL is mounted by snapping on a 10 × 3 mm bus bar.

Advantages & Benefits

- Large contact area
- Simple and tool-free mounting, easy assembly
- The spring design requires no adjustments and will permanently maintain contact to the cable shield
- Shock and vibration resistant, maintenance free
- Designed for high density applications

Specifications

Material

SKL-clamp Spring steel, zinc plated

PFS2-foot Spring steel

Bus bar Cu, tin plated, max. current: 140 Amps

Accessories

MF Supports for bus bars 187