icotek

PFSZ|SKL

EMC Shield Clamps for Bus Bar



Product Description

Comparable with the PFS|SKL range, the PFSZ|SKL shield clamps are easy to use and effective in grounding single cable shields. They are used for mounting on 10 × 3 mm bus bars.

The PFSZ range provides the possibility to fix the cable with a cable tie. Strain relief in accordance with EN 62444 is achieved.

Advantages & Benefits

- Integrated strain relief
- Large contact area

4

- Simple and tool-free mounting, easy assembly
- The spring design requires no adjustments and will permanently maintain contact to the cable shield
- Shock and vibration resistant, maintenance free

Specifications

Material

SKL-clamp	Spring steel, zinc plated
PFSZ-foot	Spring steel
Bus bar	Cu, tin plated, max. current: 140 Amps

Accessories

KEL-EMC-PF Bracket	139
MF Supports for bus bars	187



Туре	Order No.	Shield diameter	PU
PFSZ-M MSKL 3-12	37630	3 - 12 mm 0.118 - 0.472 "	10
PFSZ-M MSKL 8-18	37632	8 - 18 mm 0.315 - 0.709 "	10
PFSZ SKL 1.5-3	36787.1	1.5 - 3 mm 0.059 - 0.118 "	10
PFSZ SKL 3-6	36787.2	3 - 6 mm 0.118 - 0.236 "	10
PFSZ SKL 6-8	36787.3	6 - 8 mm 0.236 - 0.315 "	10
PFSZ SKL 8-11	36787.4	8 - 11 mm 0.315 - 0.433 "	10
Bus bar 10 × 3 mm / 39.37 x 0.394 "	36100	10 × 3 × 1000 mm* 39.37 x 0.394 x 0.118 "	1

* Other lengths available on request