

# SFZ|SKL

## EMC Shield Clamps for 35 mm DIN Rail



Type	Order No.	Shield diameter	PU
SFZ-M MSKL 3-12	37620	3 - 12 mm 0.118 - 0.472 "	10
SFZ-M MSKL 8-18	37622	8 - 18 mm 0.315 - 0.709 "	10
SFZ SKL 1.5-3	36850	1.5 - 3 mm 0.059 - 0.118 "	10
SFZ SKL 3-6	36855	3 - 6 mm 0.118 - 0.236 "	10
SFZ SKL 6-8	36860	6 - 8 mm 0.236 - 0.315 "	10
SFZ SKL 8-11	36865	8 - 11 mm 0.315 - 0.433 "	10
SFZ SKL 11-17	36870	11 - 17 mm 0.433 - 0.669 "	10
SFZ SKL 17-22	36875	17 - 22 mm 0.669 - 0.866 "	10
SFZ SKL 22-30	36880	22 - 30 mm 0.866 - 1.181 "	10
SFZ SKL 30-38	<b>NEW</b> 36885	30 - 38 mm 1.181 - 1.496 "	10

### Product Description

The shield clamps SFZ|SKL are easy to use and effective in grounding single cable shields in combination with strain relief.

Cables are secured with a cable tie. Strain relief in accordance with EN 62444 is achieved.

For assembly on 35 mm DIN rails.

### Advantages & Benefits

- Simple and tool-free mounting, easy assembly
- Shock and vibration resistant, maintenance free
- Strain relief of the cable and grounding in a single device
- Large contact area
- The spring design requires no adjustments and will permanently maintain contact to the cable shield

### Specifications

#### Material

SKL-clamp      Spring steel, zinc plated  
SF- / SFZ-foot      Spring steel