

ST-B Plugs for Membranes



Type	Order No.	Diameter D1	Diameter D2	Length L	PU
ST-B 6	42806	8 mm 0.315 "	6 mm 0.236 "	16 mm 0.63 "	25
ST-B 10	42810	12 mm 0.472 "	10 mm 0.394 "	16 mm 0.63 "	25
ST-B 12	42812	15 mm 0.591 "	12 mm 0.472 "	16 mm 0.63 "	25
ST-B 16	42816	19 mm 0.748 "	16 mm 0.63 "	16 mm 0.63 "	25
ST-B 22	42822	25 mm 0.984 "	22 mm 0.866 "	21 mm 0.827 "	25
Assortment ST-B Plugs	42801	5× ST-B 6 5× ST-B 10 2× ST-B 12 1× ST-B 16 1× ST-B 22			

Product Description

Plugs ST-B are used to seal already pierced membranes in various cable entry plates (KEL-DPU / KEL-DPZ / KEL-DP / KEL-QTA-DP) and DT grommets.

Perfect for applications where cables have been removed.

The IP rating of the cable entry plate remains.

Advantages & Benefits

- Sealing of pierced cable entry membranes which are no longer in use

Specifications

Material	Polyamide (PA), white
Flame class	UL94-Vo
Operating temperature	- 40°C to + 120°C - 40°F to + 248°F
Properties	Halogen-free, silicone-free

Compatible with

KEL-DPU Cable entry plates	76 - 77
KEL-DPZ Cable entry plates	78 - 84
KEL-DP Cable entry plates	86 - 89
DT Cable entry grommets	52
KEL-QTA-DP Cable entry plates	64