

Mounting Console with Fixed Limit Stop for M30 × 1,5; Semi-Flush Mounting

Z30M002

Part Number




Technical Data

Mechanical Data

Material	Stainless Steel; Plastic
Threaded sleeve tightening torque	max. 6 Nm
Clamp retainer tightening torque	4 Nm
Packaging unit	1 Piece
Mounting Number	132



Legend					
+	Supply Voltage +	nc	Not connected	EN _{BNS422}	Encoder B/B (TTL)
-	Supply Voltage 0 V	U	Test Input	EN _A	Encoder A
~	Supply Voltage (AC Voltage)	Ū	Test Input inverted	EN _B	Encoder B
A	Switching Output (NO)	W	Trigger Input	AM _{IN}	Digital output MIN
Ā	Switching Output (NC)	W-	Ground for the Trigger Input	AM _{AX}	Digital output MAX
V	Contamination/Error Output (NO)	O	Analog Output	Aok	Digital output OK
Ṽ	Contamination/Error Output (NC)	O-	Ground for the Analog Output	SY _{IN}	Synchronization In
E	Input (analog or digital)	BZ	Block Discharge	SY _{OUT}	Synchronization OUT
T	Teach Input	Amv	Valve Output	OL _r	Brightness output
Z	Time Delay (activation)	a	Valve Control Output +	M	Maintenance
S	Shielding	b	Valve Control Output 0 V	rsv	Reserved
RxD	Interface Receive Path	SY	Synchronization	Wire Colors according to DIN IEC 60757	
TxD	Interface Send Path	SY-	Ground for the Synchronization	BK	Black
RDY	Ready	E+	Receiver-Line	BN	Brown
GND	Ground	S+	Emitter-Line	RD	Red
CL	Clock	⊕	Grounding	OG	Orange
E/A	Output/Input programmable	SnR	Switching Distance Reduction	YE	Yellow
	IO-Link	Rx+/-	Ethernet Receive Path	GN	Green
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path	BU	Blue
IN	Safety Input		Interfaces-Bus A(+)/B(-)	VT	Violet
OSSD	Safety Output	La	Emitted Light disengageable	GY	Grey
Signal	Signal Output	Mag	Magnet activation	WH	White
BL_D+/-	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation	PK	Pink
EN _{0 RS422}	Encoder 0-pulse 0/0 (TTL)	EDM	Contact Monitoring	GNYE	Green/Yellow
PT	Platinum measuring resistor	EN _{AR422}	Encoder A/Ā (TTL)		