

Top Mounted Strobe



OPTIONS & ACCESSORIES

The Top Mounted Strobe is a factory installed option that is available at the time of order of the DCC and FCS Controllers. This high powered, red LED flashing beacon offers excellent flash intensity, durable vibration resistant construction and a long life. It is made of polycarbonate and has an IP65 rating.

Ideal for refrigeration applications; when combined with the Manual Shutoff Switch, meets B52 code requirements. May be used in emergency shutdowns, ventilation purges and other similar practices.

NOTE: The Top Mounted Strobe does not have an audible feature.

KEY FEATURES

- » Lightweight, durable
- » Weather and corrosion resistant
- » Excellent flash intensity
- » 4 User selectable flash patterns

APPLICATIONS

- » Parking Garages
- » Refrigeration Plants
- » Equipment/ Machinery Rooms
- » Manufacturing Plants
- » Food Processing Plants
- » Power Generation Plants
- » ... and many more

CET COMPATIBLE PRODUCTS

FCS Flexible Control System Controller

DCC Dual Channel Controller

TECHNICAL SPECIFICATIONS

MECHANICAL

Enclosure	PC cover and base
Size	6.1 cm dia x 13 cm H 2.4 in dia x 5.2 in H
Lens Colour	Red
# of Flash Patterns	4

USER INTERFACE

Push Button Switch	Push to change flash patterns
--------------------	-------------------------------

ELECTRICAL

Operation Voltage	10 - 30 VDC
Power	0.3 W

ENVIRONMENTAL

Operating Temperature	-20°C to 65°C (-4°F to 149°F)
-----------------------	-------------------------------

CERTIFICATION

IP65 rated
Certification requirements are met if this device is connected to a CSA approved CET Controller, Self Contained Controller, Transmitter or a CSA approved Class 2 power supply

PRODUCT CODES

OPTION (Factory installed) Add at the end of the product "Part Number".

- L	Top Mounted Strobe (factory installed on Controller at time of order)
-----	---

