

CHARACTERISTICS

Ambient temperature	-10 ÷ -70 °C	
Fluid	filtered air 50 µm, with or without lubrication	
Commutation system	poppet	
Max pressure	10 bar	
Connections	G1/8	G1/4
Nominal bore (mm)	2,3	8
Nominal flow rate (NI/min)	98	800
PNEUMATIC FOOT VALVE:		
Valve body	zamak	
Foot valve lever	aluminium	
Pedal body and protection	plastic material with reinforcing steel plate	
Seals	oil and wear resistant compound	
Spool	aluminium	
SOLENOID FOOT VALVE		
Valve body, foot valve lever, protection	dielectric plastic material	



Pneumatic foot valve G1/4 with protection

- Spring return
 - AM-5000
 - AM-5001
 - AM-5002
- External operation - Spring return
 - AM-5021

- Bistable
 - AM-5003
 - AM-5004
 - AM-5005
- External operation - bistable
 - AM-5031

- With safety control
 - AM-5015
 - AM-5011
 - AM-5012
- External operation with safety control
 - AM-5041

Pneumatic foot valve G1/4 without protection

- Spring return
 - AM-5000A
 - AM-5001A

- Bistable
 - AM-5003A
 - AM-5004A

Pneumatic foot valve G1/8 with protection

- Spring return
 - AM-5043
 - AM-5043B
 - AM-5043C
 - AM-5043D

Solenoid foot valve

- AM-5050
No electrical microswitch
- AM-5051
Electrical microswitch
- AM-5052
Double electrical microswitch

Version without protection available upon request